

TECHNICAL DATA SHEET MINI RECORD FASTENER

TECHNICAL DATA

CHOOSE YOUR FASTENER


Fastener size	Belt thickness		Ø minimum drum		Maximum Operating tension		Construction	Staples	Pin	Installation
	mm	inch	mm	inch	N/mm	PIW				
MR1	1.5 - 3.2	1/16 - 1/8	50	2	20	115	GALVANIZED STEEL or STAINLESS STEEL	STAINLESS STEEL	Flexible coated stainless steel pin Ø2.1	Hammer ; Optinnal MLT Quick Driver installation tool
MR2	3 - 5	1/16 - 3/16	75	3	32	185			Flexible coated stainless steel pin Ø3.6	
MR3	4.8 - 6.4	3/16 - 1/4	100	4	40	230			Flexible coated stainless steel pin Ø5.1	

IN OPTION, CHOOSE YOUR ADDITIONAL RETAINING WASHERS AND CABLES

MR1 / MR2 / MR3

Bag of 100 units

Retaining washers for MR fasteners available on request



PACKAGING

According to your needs

PER BOX OF 4 JUNCTIONS

le kit contient :

- 4 fasteners at the length adapted to the width of your belt (600, 900, 1000, 1050, 1200, 2000, 3000 mm),
- Stainless steel staple,
- Flexible coated stainless steel pin, adapted to your fastener length and size.

PER CASE OF 48 JUNCTIONS

le kit contient :

- 48 fasteners at the length adapted to the width of your belt (600, 900, 1000, 1050, 1200, 2000, 3000 mm),
- Stainless steel staple,
- Pin to be ordered separately, 30m roll available.



For any support in the installation of our products or in the resolution of problems on your conveyor belt, benefit from our **HOTLINE service** in real time.

Registration on www.mlt-lacing.com/mlt-hotline

Distributor logo

PATENTED PRODUCT
MADE IN FRANCE

 **MLT GROUP**
Conveyor Solutions Expert

 **MLT GROUP**
Minet Lacing Technology

 **TECHNICGUM**
MLT GROUP

www.mltgroup-conveyor.com - info@mltgroup-conveyor.com