







TECHNICAL DATA SHEET RIVETS FASTENERS

SELECT A RIVET FASTENER

7 fastener types available















Mini-prestol

Presto

Minibelt

Airport

Gemini

A

DK

	Belt thickness		Operating voltage		Mini pulley ø		Failure stress		Number of
	mm	inch	N/mm	PIW	mm	inch	N/mm	PIW	rivets per meter
Miniprestol	1 - 2	3/64 - 5/64	8	45	20	25/32	80	457	240
Prestol	1.5 - 3	1/16 - 1/8	12	68	25	63/64	120	685	200
Minibelt	2 - 4	5/64 - 5/32	20	114	30	1 ^{3/16}	200	1142	160
Airport	3 - 6	1/8 - 9/32	20	114	35	1 ^{3/8}	200	1142	160
Gemini	3 - 7	1/8 - 9/32	35	200	60	2 ^{23/64}	350	2000	160
А	5 - 7	3/16 - 9/32	35	200	75	261/64	350	2000	96
BR	6 - 11	7/32 - 7/16	60	340	125	4 ^{59/64}	600	3426	76

PACKAGING

According to your needs

AT THE UNIT*

the kit contains :

- 1 fastener at the length adapted to the width of your belt,
- number of rivets adapted to your fastener length and size,
- coated rigid pin, adapted to your fastener length and model, flexible pin for rivet A and BR.

PER BOX OF 4 JUNCTIONS*

the kit contains :

- 4 fasteners at the length adapted to the width of your belt,
- number of rivets adapted to your fastener length and size,
- coated rigid pin, adapted to your fastener length and model, flexible pin for rivet A and BR.

PER CASE OF 48 JUNCTIONS*

the kit contains :

- 48 fasteners at the length adapted to the width of your belt,
- Pins and rivets to be ordered separately,

*Fasteners and pins available in steel or stainless steel. Copper Rivets. Different lengths possible depending on clip model : consult us.



For any support in the installation of our products or in the resolution of problems on your conveyor belt, benefit from our **HOTLINE service** in real time.

Registration on www.mlt-lacing.com/mlt-hotline





