

# TECHNICAL DATA

## RV6 / SERIE G FASTENERS

### TECHNICAL DATA

#### RV6 FASTENERS

##### Metric

Belt thickness (mm)	6 - 12
Maximum Operating tension (N/mm)	1050
Ø minimum drum (mm)	230
Fasteners	Carbon steel
Spikes Ø x length (mm)	galvanised steel staples : <ul style="list-style-type: none"> <li>• 2.9 x 32</li> </ul>
Connecting pin (mm)	Flexible polyamide coated stainless steel pin Ø7

##### Imperial

Belt thickness (inch)	7/32" - 15/32"
Maximum Operating tension (PIW)	600
Ø minimum drum (inch)	9"
Fasteners	Carbon steel
Spikes Ø x length (inch)	galvanised steel staples : <ul style="list-style-type: none"> <li>• 1/8" x 1 1/4"</li> </ul>
Connecting pin (inch)	Flexible polyamide coated stainless steel pin Ø1/4"

#### SERIE G FASTENERS

Metric	G 2002	G 2003
Belt thickness (mm)	7.5 - 12	12 - 20
min pulley diameter (mm)	250	500
Maximum Operating tension (N/mm)	1400	3500
Fastener quality	Fasteners in high resistance steel with pre-assembly staples treated stainless steel	Fasteners in high resistance steel, staples in carbon
Staples Ø x length (mm)	Staples sizes : <ul style="list-style-type: none"> <li>• 2.3 x 23</li> <li>• 2.3 x 25</li> <li>• 2.3 x 27</li> </ul>	Staples sizes : <ul style="list-style-type: none"> <li>• 2.8 x 29</li> <li>• 2.8 x 38</li> </ul>
Connecting pin	Reinforced cable in stainless steel coated in polyamide (to be ordered separately)	
Installation	Hammer or pneumatic tool	

Imperial	G 2002	G 2003
Belt thickness (inch)	19/64" - 1/2"	1/2" - 25/32"
min pulley diameter (inch)	10"	20"
Maximum Operating tension (PIW)	800	2000
Fastener quality	Fasteners in steel high resistance with pre-assembly spikes treated stainless steel	Fasteners in steel high resistance, spikes in carbon
Staples Ø x length (inch)	Staples sizes : <ul style="list-style-type: none"> <li>• 1/16" x 15/16"</li> <li>• 1/16" x 1"</li> <li>• 1/16" x 1 1/16"</li> </ul>	Staples sizes : <ul style="list-style-type: none"> <li>• 1/8" x 1 1/8"</li> <li>• 1/8" x 1 1/2"</li> </ul>
Connecting pin	Reinforced cable in stainless steel coated in polyamide (to be ordered separately)	
Installation	Hammer or pneumatic tool	



For any support in the installation of our products or in the resolution of problems on your conveyor belt, benefit from our **HOTLINE service** in real time.

Registration on [www.mlt-lacing.com/mlt-hotline](http://www.mlt-lacing.com/mlt-hotline)

# PACKAGING

Depending on your needs

## RV6 FASTENERS

### PER UNIT\*

The kit contains :

- 1 complete fastener adapted to the width of your belt (800, 1000, 1200, 1350 mm),
- Adapted galvanised steel staples,
- Flexible coated stainless steel polyamide pin diameter 7mm, adapted to the length of your fastener.

## SERIE G FASTENERS

### PER UNIT\*

The kit contains :

- 1 fastener cut to the length, adapted to the width of your belt (1000, 1050, 1200, 1600, 1800 mm)\*,
- adapted staples, treated galvanised steel or bezinal steel,
- pin to be ordered separately.

### PER BOX OF 4 FASTENERS\*

The kit contains :

- 4 complete fasteners adapted to the width of your belt (800, 1000, 1200, 1350 mm),
- Adapted galvanised steel staples,
- Flexible coated stainless steel polyamide pin diameter 7mm, adapted to the length of your fastener.

*\*Available for some fasteners models: consult us*



PATENTED PRODUCT  
MADE IN FRANCE

[www.mltgroup-conveyor.com](http://www.mltgroup-conveyor.com) - [info@mltgroup-conveyor.com](mailto:info@mltgroup-conveyor.com)