

INSTALLATION METHOD


How do I install my Bolt plate fastener?



1| Cut the belt at right angles.



2| Align the 2 ends of the belt.
Nail the drilling template in several places on the belt.



3| With the power drill driver and the appropriate die-cutter, drill the holes for the bolts.
Remove the nails and the template.




4| Turn one side of the belt over and insert the first row of bolts into the holes.



5| Place the serrated edge of the template on the 2nd row of bolts.



6| Drive the screws deep into the belt. Place a wedge between the bolts and give some light hammer taps.



7| Install the plates of the fasteners.



8| Put the nuts on all the screws.



9| Tighten the nuts* with the drill driver equipped with the tightening key, alternating the 2 ends.



10| Break the ends of the bolts with the 2 tubes break bolts.



YOUR MLT BOLT PLATE FASTENERS ARE INSTALLED

*The nuts are tightened with a torque limiter until the maximum torque is reached.

REQUIRED MATERIALS

to install its bolt plate fastener easily

These are the tools needed to quickly and easily install your **bolt plate fastener**.



Appropriate bolt plate fastener



Power drill



Set square



Hammer



Drilling template**



Punch**



Tightening key**



Two bolt breaker tubes**

**All of these tools are available in MLT's tool catalogue.*

***To be selected accordingly to the plate fastener size required.*

PPE recommended by MLT



Light protection goggles



Safety shoes



Cut resistant gloves



Safety helmet



For any support in the installation of our products or solutions to problems from your conveyor belt, you can contact our **HOTLINE service**.

Registration on www.mltgroup-conveyor.com/mlt-service

Distributor logo

PATENTED PRODUCT
MADE IN FRANCE

 **MLT GROUP**
Conveyor Solutions Expert

www.mltgroup-conveyor.com - info@mltgroup-conveyor.com