





CHOOSE EASILY YOUR CLIP'N LOCK™



	CL™25	CL™30	CL™40	CL™50
Lacing pitch, mm	2.54	2.54	3.175	3.67
Belt thickness, mm (Regular point)	1 - 1.5	1.5 - 2	2 - 3	3 - 5
Min. pulley Ø, mm	Ø 20	Ø 30	Ø 40	Ø 60
Failure stress, N/mm	40	68	99	115
Steel quality	316 L Stainless steel	316 L Stainless steel	316 L Stainless steel	316 L Stainless steel
Cable pin	Stainless steel rod [Nylon coated or not] in stainless steel Ø 1 mm	Stainless steel rod or bare [Nylon coated or not] in stainless steel Ø 1.5 – 1.8 mm	Stainless steel rod or bare [Nylon coated or not] in stainless steel Ø 1.8 – 2.1 mm	Stainless steel rod or bare [Nylon coated or not] in stainless steel Ø 2.1 – 2.6 mm
Available combs, mm	350 (14'') - 600 (24'')	350 (14'') - 600 (24'') - 1200 (48'')	350 (14'') - 600 (24'') - 1200 (48'')	350 (14'') - 600 (24'') - 1200 (48'')
Fastener length available, mm	300 (12'') - 600 (24'')	300 (12'') - 600 (24'') - 1200 (48'')	300 (12'') - 600 (24'') - 1200 (48'')	300 (12'') - 600 (24'') - 1200 (48'')

PATENTED PRODUCT

MADE IN FRANCE

PACKAGING

According to your needs

PER BOX OF 4 JUNCTIONS

the kit contains:

■ 4 fasteners at the length* adapted to the width of your belt:

300 - 600 mm for $CL^{TM}25 \text{ models}$,

300 - 600 - 1200 mm for $CL^{TM}30 - 40 - 50 \text{ models}$.

■ Pins to be ordered separately.

*Lengths available according to Clip'N Lock™ models. Some lengths are available on request: contact us.

PER CASE OF 48 JUNCTIONS

the kit contains:

■ 48 fasteners at the length* adapted to the width of your

300 - 600 mm for $CL^{TM}25 \text{ models}$,

 $300 - 600 - 1200 \text{ mm for } CL^{TM}30 - 40 - 50 \text{ models.}$

Pins to be ordered separately.

MLT GROU Conveyor Solutions Expert

Distributor logo

