

The 1st generation of flexible rubber splices which significantly reduces your downtime

+ SUPER-SCREW[®] ORIGINAL, the innovative and fast solution for splicing your belts

When making a belt endless, you may be exposed to certain types of problems.

This patented, incomparable splice provides the solution to your installation problems. Furthermore it can withstand tensions up to **2500 N/mm**.

Thanks to the screwing system, the **SUPER-SCREW[®] ORIGINAL** can be installed regardless of the :

- configuration of the conveyor belt,
- limited accessibility,
- weather conditions,
- temperature: **-30°C (-22°F)** up to **200°C (-392°F)** flash

Our **SUPER-SCREW[®] ORIGINAL** range is dedicated to EP belts greater than or equal to **2000 N/mm**.

For lower belts, please refer to our new generation **SUPER-SCREW[®]** range.

THE ADVANTAGES

- Permanent solution
- Reduces downtime of your conveyor
- Optimizes your productivity
- Easy and quick to install (1 to 2 persons)
- Self installation, low cost investment
- Leak proof and flexible
- Compatible with small pulley diameter
- Compatible with conveyor scrapers

ABRASION RESISTANT

OIL RESISTANT

FIRE RESISTANT



Incomparable fitting tolerance quality

Two material qualities of screws and inserts available

GALVANISED STEEL QUALITY

Highly resistant, the ideal choice for most situations.



STAINLESS STEEL QUALITY

Resistant to corrosive and saline environments.
For non-magnetic applications.

Technical data

Belt type N/mm	Belt cover thicknesses	Model	Abrasion resistant	Oil resistant	Fire resistant
EP 2000/5 - EP 2000/6	6+2	200	X	X	X
	6+3		X	X	X
	8+3		X	X	X
	10+3		X	X	X
>2000	6+2	250	X		X
	6+3		X		X
	8+3		X		X
	10+3		X		X

	200	250
Width of SUPER-SCREW®, mm	266	
Width to be skived on trailing edge, mm	126	
Width to be skived on leading edge, mm	140	
Top Cover Thickness, mm (± 1 mm)	8.5	10.5
Bottom Cover Thickness, mm (± 1 mm)	6	8
Screw Diameter, mm	6.3	
Number of screws required for 1 m	254	
Number of spacers required for 1 m	10	
Number of PZ Bits required for 1 m	1	

Our splicing solutions have been engineered for normal applications. For tough and abrasive environments, we encourage you to select an upper Super-Screw® size (please check specifications before)

Packaging

	ROLL PACKAGING				
	3 m roll Stainless steel only	5 m roll steel only	7.5 m roll	15 m roll	
Length of SUPER-SCREW®					
Spacers / Screws / PZ bit	to be ordered separately				
	KIT PACKAGING				
Belt width, mm (inch)	800	1000	1200	1400	1600
Length of SUPER-SCREW®	830	1045	1245	1465	1660
Spacers / Screws / PZ bit	Included				



Roll (Screws not included)



Kit (Screws included)

Installation method

**QUICK AND EASY
INSTALLATION**



INSTALLATION METHOD



VIDEO INSTALLATION METHOD

Distributor logo

MLT GROUP
Conveyor Solutions Expert

www.mltgroup-conveyor.com - info@mltgroup-conveyor.com