

RacloFlex™

N



Secondary scraper / multi-blade,
economic and polyvalent



WHY CHOOSE THE RACLOFLEX™ N ?

Structure protected for a long time


+ An ingenious system that adapts

Unlike the simple single-blade scrapers, the **RacloFlex™ N** is comprised of blades each supported by a shock absorber block which can be adjusted independently to shape the belt and compensate the faster wear of certain blades.

Faithful to its original patented design of 1985 whilst also constantly benefiting from the latest improvements and innovations, the **RacloFlex™ N** is a safe value and a rational solution for conveyor belt cleaning.



Different blades option




Dual-hardness




RacloFlex™ N and N-HD

Single blades cannot compensate for central wear



RacloFlex™ N can compensate for central wear




Other scrapers

ADVANTAGES

- Economic and polyvalent
- High performance cleaning
- Galvanised metal parts
- Toothed bearing with fast opening
- Works with 2 directions of flow
- Equipped with PE-UHMW deflector
- Dual hardness rubber technology
- Adaptable on concave or convex belts
- Many types of blades available
- Realignment of the blades by central wear compensation
- Stronger than most of the equivalent models
- Only the used blades are to be replaced
- Retractable pressurization rod
- Efficiency globally proven since 1985

OPTIONS, ACCESSORIES AND VERSIONS




Pulling pressure

Allows pressurization of scraper from above and within the angle.



Special «MultiTool key»

Gathers all the necessary functions for the manipulation and settings of the scraper.



Stainless steel Deflector

Enables the earthing of the blades (ATEX) and prevents inclusion between the blocks.

General information for the RacloFlex™ N

Quality of blade(s) :	Tungsten Carbide : 93 HRA 3x10mm	
	Or- Tungsten Carbide : 93 HRA 5x10mm	
	Or- Ceramic : Alumine frittée Al2O3 92% 10x15mm	
	Or- Stainless steel (316L/304L at choice)	
Working position :	Scraping angle = 90° (see notice)	
Surface treatment :	All electro-galvanized steel pieces + stainless A2 bolts	
Temperature :	0° / + 50° C	
Scale of pH :	4 to 10	
Maximum speed :	N	1 way = 3 m/s 2 ways = 2,5 m/s
	N -HD	1 way = 5 m/s 2 ways = 3,5 m/s
Do not expose to :	Impact and staples on tungsten carbide and ceramic (choose stainless blades)	
	Oils, grease or hydrocarbide : Special quality available	
	Corrosive atmosphere : Stainless possible on all or part	
	Uncontrolled clogging on entire scraper	



Belt, mm	500	650	800	1000	1100	1200	1400	1500	1600	1800	1900	2000	2200
Scraping width, mm	504	630	756	882	1008	1134	1260	1386	1512	1638	1764	1890	2016
Belt, inch	18	24	30	36	42	48	54	60	62	72	74	78	84
Scraping width, inch	19.8	24.8	29.8	34.7	39.7	44.6	49.6	54.6	59.5	64.5	69.4	74.4	79.4
Number of blades	4	5	6	7	8	9	10	11	12	13	14	15	16


RacloFlex™ N-HD



The heavy version **RacloFlex™ N-HD** is proposed for belts from 1400 to 2200 ; Tungsten carbide 5x10, aluminium profil block support and reinforced mechanic.

Combined use with the scraper RacloFlex™ NT





MLT Conveyor Solutions Expert
More than 70 years of innovation
at your service



www.mltgroup-conveyor.com - info@mltgroup-conveyor.com